



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**



**3/8" BOLTS**

Use these special four bolts supplied in the center manifold holes (use thread sealant). Tighten these four first, using a torque wrench and a 3/8" swivel socket or a 3/8" box/open end wrench. If using a box wrench, estimate the torque compared to other bolts.

**W509**